

A Bluffers Guide to SQL Injection

Assume an SQL Statement for

selecting all users with "userName" from table "user"

Has Sony been Hacked this Week?

http://hassonybeenhackedthisweek.com/

Time-line of the Sony Hack(s) (excerpt):

2011-04-20 Sony PSN goes down

2011-05-21 Sony BMG Greece: data 8300 users (SQL Injection)

2011-05-23 Sony Japanese database leaked (SQL Injection)

2011-05-24 Sony Canada: roughly 2,000 leaked (SQL Injection)

2011-06-05 Sony Pictures Russia (SQL Injection)

2011-06-06 Sony Portugal: SQL injection, iFrame injection and XSS

2011-06-20 20th breach within 2 months

177k email addresses were grabbed via a SQL injection

(http://hassonybeenhackedthisweek.com/history

Consequences:

- account data of close to 100 million individuals exposed
- · over 12 million credit and debit cards compromised
- more than 55 class-action lawsuits
- costs of \$ 170 million only in 2011

© 2014 SAP AG. All Rights Reserved.

Page 3 of 18

A Bluffers Guide to SQL Injection

Assume an SQL Statement for

stmt = "SELECT * FROM 'users' WHERE 'name' = '" + userName + "';"

© 2014 SAP AG. All Rights Reserved. Page 4 of 18 © 2014 SAP AG. All Rights Reserved. Page 4 of 18

A Bluffers Guide to SQL Injection

Assume an SQL Statement for

```
stmt = "SELECT * FROM 'users' WHERE 'name' = '" + userName + "';"
```

What happens if we choose the following userName:

```
userName = "' or '1'='1"
```

A Bluffers Guide to SQL Injection

Assume an SQL Statement for

```
stmt = "SELECT * FROM 'users' WHERE 'name' = '" + userName + "';"
```

What happens if we choose the following userName:

```
userName = "' or '1'='1"
```

• Resulting in the following statement:

```
stmt = "SELECT * FROM 'users' WHERE 'name' = '' or '1'='1';"
```

© 2014 SAP AG. All Rights Reserved.

Page 4 of 18

A Bluffers Guide to SQL Injection

Assume an SQL Statement for

```
stmt = "SELECT * FROM 'users' WHERE 'name' = '" + userName + "';"
```

What happens if we choose the following userName:

```
userName = "' or '1'='1"
```

Resulting in the following statement:

```
stmt = "SELECT * FROM 'users' WHERE 'name' = '' or '1'='1';"
```

Which is equivalent to


```
stmt = "SELECT * FROM 'users';"
```

selecting the information of all users stored in the table 'users'!

© 2014 SAP AG. All Rights Reserved.

Page 4 of 18

Vulnerability types of CVE reports since 1999



- Causes for most vulnerabilities are
 - programming errors
 - configuration errors
- Patching is
 - expensive
 - may introduce new bugs


How can we ensure that no vulnerable code is shipped?

© 2014 SAP AG. All Rights Reserved. Page 4 of 18 © 2014 SAP AG. All Rights Reserved. Page 5 of 18

Finding Security Vulnerabilities

Find Vulnerabilities Using the Running Application Manual Application Manual Security Code Review Automated Application Vulnerability Scanning Automated Static Code Analysis


Finding Security Vulnerabilities



© 2014 SAP AG. All Rights Reserved.

Page 6 of 18

Evolution of Source Code



- Increase in
- code size

number of products


code complexity

product versions

© 2014 SAP AG. All Rights Reserved.


Page 6 of 18

SAST as Part of SAP's SDL



© 2014 SAP AG. All Rights Reserved. Page 7 of 18 © 2014 SAP AG. All Rights Reserved. Page 8 of 18

SAST as Part of SAP's SDL



So Everything is Secure Now, Right?

Our tool reports all vulnerabilities in your software - you only need to fix them and you are secure.

Undisclosed sales engineer from a SAST tool vendor.

Yes, this tools exists! It is called Code Assurance Tool (cat):

So Everything is Secure Now, Right?



Our tool reports all vulnerabilities in your software – you only need to fix them and you are secure.

Undisclosed sales engineer from a SAST tool vendor.

© 2014 SAP AG. All Rights Reserved.

Page 9 of 18

So Everything is Secure Now, Right?

Our tool reports all vulnerabilities in your software - you only need to fix them and you are secure.

Undisclosed sales engineer from a SAST tool vendor.

Yes, this tools exists! It is called Code Assurance Tool (cat):

• The cat tool reports each line, that might contain a vulnerability:

brucker@fujikawa – /usr/src/modules/tp-smapi rucker@fujikawa:/usr/src/modules/tp-smapi\$ cat thinkpad_ec.c include <linux/kernel.h> #include <linux/module.h>
#include <linux/dmi.h> static int thinkpad_ec_request_row(const struct thinkpad_ec_row *args) u8 str3; int i; /* EC protocol requires write to TWR0 (function code): */ if (!(args->mask & 0x0001)) {
 printk(KERN ERR MSG FMT("bad args->mask=0x%02x", args->mask));

Page 9 of 18

So Everything is Secure Now, Right?


44

Our tool reports all vulnerabilities in your software – you only need to fix them and you are secure.


Undisclosed sales engineer from a SAST tool vendor.

Yes, this tools exists! It is called Code Assurance Tool (cat):

- The cat tool reports each line, that might contain a vulnerability:
- It supports also a mode that reports no false positives:



SAST Solutions Applied at SAP



- Mandatory for all products
- Multiple billions lines analyzed

Language	Tool	Vendor
ABAP	CVA (SLIN_SEC)	SAP
C/C++	Coverity	Coverity
Others	Fortify	HP


Other important pillars of SAP's SDL:

- · Secure programming training's
- · Pen tests on the final product

In addition:

- Own research (e.g., JS, Mobile)
- Ongoing evaluation of
 - alternative tools and
 - complementary techniques.

Continuous Improvements



Further input channels:

- Development teams
- Internal research
- Scan reviews
- Code reviews

•

© 2014 SAP AG. All Rights Reserved.

Page 10 of 18

Open Issues

- · Estimating the risk of not fixing security issues is hard
 - How to prioritize security vs. functionality
 - In case of doubt, functionality wins
- Pushing SAST across the software supply chain
 - Consumed software (OSS, third-party products)
 - SAP Customers, partners, and OEM products
- Huge and hybrid multi-language applications
 - Client-server applications
 - Web-frameworks
- Dynamic programming paradigms and languages
 - JavaScript, Ruby, etc.
- Lack of standardized regression test suites
 - Different tools
 - Different versions of the same tool

© 2014 SAP AG. All Rights Reserved. Page 11 of 18 © 2014 SAP AG. All Rights Reserved. Page 12 of 18

Lessons Learned: Recommendations (1/3)

Follow the recommendations given by Chandra et al:

- Start small
 - Start with one pilot
 - Succeed with pilot before larger roll-out
- Go for the throat
 - Start with the main security threat
- Appoint a champion
 - Identify a developer that knows all parts of the application
 - Make this developer your tool champion
- Measure the outcome
 - Track and measure the generated data
- Make it your own
 - Adapt the tool to your needs
 - SAST tools are not "off-the-shelf" products

© 2014 SAP AG. All Rights Reserved.

Page 13 of 18

Lessons Learned: Recommendations (3/3)

- Plan your changes and updates
 - All changes to the tools might change the results
- Do get support (and commitment) from your management
 - Introducing SAST will cost money and effort
 - Minimize the risk of discussing "security vs. features"
- Do not stop here.
 - Introducing SAST is only the first step
 - Use complementary techniques, e.g.,
 - Threat modeling
 - Dynamic testing tools
 - Penetration tests

. . .

Lessons Learned: Recommendations (2/3)

Based on our experiences, we add:

- Plan and invest enough resources
 - Introducing SAST requires significant resources
 - Integration, Analysis, Education, . . .
- Plan and invest enough infrastructure
 - · If the tools are slow, nobody will use them
- Do understand your developers as your friends
 - Do not follow the "security review" model
 - SAST tools should be understood as "debug tool"
- Execute scans regularly
 - SAST is not a one-time effort

© 2014 SAP AG. All Rights Reserved.

Page 14 of 18

Conclusion

44

You cannot pay people well enough, to do proper code audits.

I tried it.

Yaron Minsky, Jane Street Capital

- We can confirm the results of Scandariato et al that show that SAST is the most effective and efficient security testing method
- Embed your SAST efforts into a holistic security testing strategy

© 2014 SAP AG. All Rights Reserved. Page 15 of 18 © 2014 SAP AG. All Rights Reserved. Page 16 of 18

Thank you!



OH, DEAR - DID HE BREAK SOMETHING?



DID YOU REALLY NAME YOUR SON Robert'): DROP TABLE Students: -- ? OH, YES, LITTLE BOBBY TABLES,

WE CALL HIM.

WELL, WE'VE LOST THIS YEAR'S STUDENT RECORDS. I HOPE YOU'RE HAPPY. AND I HOPE ~ YOU'VE LEARNED TO SANITIZE YOUR DATABASE INPUTS.

http://xkcd.com/327/



© 2014 SAP AG. All rights reserved

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors Microsoft, Windows, Excel, Outlook, and PowerPoint are registered trademarks of Microsoft Corporation.

IBM, DB2, DB2 Universal Database, System i, System i5. System p OS/400, AS/400, S/390 Parallel Enterprise Server, PowerVM, Power Architecture, POWER6+, POWER6, POWER5+, POWER5, POWER, OpenPower, PowerPC, BatchPipes, BladeCenter, System Storage, GPFS, HACMP, RETAIN, DB2 Connect, RACF, Redbooks, OS/2, Parallel Sysplex, MVS/ESA, AIX, Intelligent Miner, WebSphere, Netfinity, Tivoli and Informix

are trademarks or registered trademarks of IBM Corporation Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

Adobe, the Adobe logo, Acrobat, PostScript, and Reader are either trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Oracle is a registered trademark of Oracle Corporation UNIX, X/Open, OSF/1, and Motif are registered trademarks of the Open

Citrix, ICA, Program Neighborhood, MetaFrame, WinFrame, VideoFrame, and MultiWin are trademarks or registered trademarks of Citrix Systems.

HTML XML XHTML and W3C are trademarks or registered trademarks of W3C®, World Wide Web Consortium, Massachusetts Institute of

Technology. Java is a registered trademark of Sun Microsystems, Inc. JavaScript is a registered trademark of Sun Microsystems, Inc., used under license for technology invented and implemented by Netscape. SAP, R/3, SAP NetWeaver, Duet, PartnerEdge, ByDesign, SAP BusinessObjects Explorer, StreamWork, and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries

Business Objects and the Business Objects logo, BusinessObjects, Crystal Reports, Crystal Decisions, Web Intelligence, Xcelsius, and other Business Objects products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of Business Objects Software Ltd. Business

Sybase and Adaptive Server, iAnywhere, Sybase 365, SQL Anywhere, and other Sybase products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of Sybase, Inc. Sybase is an SAP

All other product and service names mentioned are the trademarks of their respective companies. Data contained in this document serves informational purposes only. National product specifications may vary.

The information in this document is proprietary to SAP. No part of this document may be reproduced, copied, or transmitted in any form or for any purpose without the express prior written permission of SAP AG.

This document is a preliminary version and not subject to your license agreement or any other agreement with SAP. This document contains only intended strategies, developments, and functionalities of the SAP® product and is not intended to be binding upon SAP to any particular course of business, product strategy, and/or development. Please note that this document is subject to

change and may be changed by SAP at any time without notice. SAP assumes no responsibility for errors or omissions in this document. SAP does not warrant the accuracy or completeness of the information, text, graphics, links, or other items contained within this material. This document is provided without a warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement.

SAP shall have no liability for damages of any kind including without limitation direct, special, indirect, or consequential damages that may result from the use of these materials. This limitation shall not apply in cases of intent or gross

The statutory liability for personal injury and defective products is not affected. SAP has no control over the information that you may access through the use of hot links contained in these materials and does not endorse your use of third-party Web pages nor provide any warranty whatsoever relating to third-party Web pages.

© 2014 SAP AG. All Rights Reserved.

Bibliography I



Ruediger Bachmann and Achim D. Brucker.

Developing secure software: A holistic approach to security testing.

Datenschutz und Datensicherheit. March 2014.



Achim D. Brucker and Uwe Sodan.

Deploying static application security testing on a large scale.

In ai Sicherheit 2014, Lecture Notes in Informatics, ai. March 2014,

© 2014 SAP AG. All Rights Reserved.

Page 18 of 18